

Easystart Part No.	Volts	Capacity AH @ 20HR	C.C.A. (SAE)	C.C.A. (EN2)	Plates per cell	Reserve capacity (minutes)	Dimensions (Metric)			Dimensions (Imperial)			Weight (kg)	Layout	Terminal type	Hold down
							L	W	H	L	W	H				
12N24-3	12	26	330	310	9	30	184	126	173	7.25	4.96	6.81	7.2	0	T4	N
12N24-4	12	26	330	310	9	30	184	126	173	7.25	4.96	6.81	7.2	1	T4	N
002R	12	38	390	370	9	48	175	175	190	6.88	6.88	7.48	7.9	1	T1 post	B3
002L	12	38	390	370	9	48	175	175	190	6.88	6.88	7.48	7.9	0	T1 post	B3
004L	12	50	380	360	9	75	202	173	225	7.95	6.81	8.85	14.2	0	T1 post	N
004R	12	50	380	360	9	75	202	173	225	7.95	6.81	8.85	14.2	1	T1 post	N
005L	12	60	570	530	11	90	230	175	225	9.05	6.88	8.85	15.6	0	T1 post	N
005R	12	60	570	530	11	90	230	175	225	9.05	6.88	8.85	15.6	1	T1 post	N
015	12	40	410	380	10	60	236	132	197	9.29	5.19	7.75	13.1	1	T1 post	B12
017	12	90	770	720	17	150	350	175	175	13.78	6.88	6.88	22.8	0	T1 post	B3
019	12	100	880	820	19	165	350	175	190	13.78	6.88	7.48	23.8	0	T1 post	B3
O19L	12	110	980	920	TBA	208	393	175	190	15.47	6.88	7.48	25.8	0	T1 post	B3
027	12	62	570	520	12	105	246	175	190	9.68	6.88	7.48	15.5	0	T1 post	B3
037	12	38	360	340	9	50	236	132	197	9.29	5.19	7.75	11.3	0	T4F	B12
038	12	38	360	340	9	50	236	132	197	9.29	5.19	7.75	11.3	1	T1 post	B12
O47	12	32	230	200	TBA	35	173	135	225	6.81	5.31	8.85	10.9	0	T1 post	B1
O48	12	40	380	360	10	60	236	126	225	9.29	4.96	8.85	12.9	0	T1 post	B1
O49	12	40	380	360	10	60	236	126	225	9.29	4.96	8.85	12.9	1	T1 post	B1
O54	12	38	360	330	9	38	195	125	225	7.67	4.92	8.85	9.9	0	T3 Post	N
054H	12	38	360	330	9	38	195	128	225	7.68	5.03	8.85	9.9	0	T3 Post	B1
O55	12	38	360	330	9	38	195	125	225	7.67	4.92	8.85	9.9	1	T3 Post	N
O56	12	45	390	370	11	48	235	126	228	9.25	4.96	8.97	12	0	T1 post	N
O57	12	45	390	370	11	48	235	126	228	9.25	4.96	8.97	12	1	T1 post	N
O58	12	45	390	370	11	48	235	126	228	9.25	4.96	8.97	12	0	T3 Post	N
O59	12	45	390	370	11	48	208	175	175	8.18	6.88	6.88	12	1	T3 Post	N
O63	12	44	410	380	9	68	208	175	175	8.18	6.88	6.88	11.6	0	T1 post	B3
O65	12	55	520	490	11	90	242	175	175	9.52	6.88	6.88	14.3	0	T1 post	B3
O66	12	71	630	600	13	135	277	175	175	10.9	6.88	6.88	18.5	0	T4F	B3
O67	12	71	630	600	13	135	277	175	175	10.9	6.88	6.88	18.5	0	T1 post	B3
O68	12	70	630	600	13	135	258	175	220	10.15	6.88	8.66	18.1	0	T1 post	B5
O69	12	70	630	600	13	135	258	175	220	10.15	6.88	8.66	18.1	1	T1 post	B5
O72	12	72	630	600	13	140	265	175	204	10.43	6.88	8.03	19.5	1	T1 post	N
O75	12	60	620	600	13	105	242	175	175	9.52	6.88	6.88	15.5	0	T1 post	B3
O77	12	44	410	380	9	68	208	175	175	8.18	6.88	6.88	11.6	1	T1 post	B3
O78	12	60	620	600	13	90	242	175	175	9.52	6.88	6.88	11.6	1	T1 post	B3
O85	12	44	410	380	9	68	208	175	175	8.18	6.88	6.88	11.6	0	T4F	B3
O88	12	70	630	600	13	135	258	168	225	10.15	6.61	8.85	18.1	0	T1 post	N
O89	12	70	630	600	13	135	258	168	225	10.15	6.61	8.85	18.1	1	T1 post	N
O96	12	75	720	680	15	130	277	175	175	10.9	6.88	6.88	18.5	0	T1 post	B3
O96R	12	75	720	680	15	130	277	175	175	10.9	6.88	6.88	18.5	1	T1 post	B3
O97	12	60	620	600	13	90	242	175	175	9.52	6.88	6.88	15	0	T4F	B3
096L	12	90	820	780	17	135	315	175	175	12.4	6.88	6.88	21.5	0	T1 post	B3
249	12	90	740	700	15	165	303	172	225	11.92	6.77	8.85	20.1	0	T1 post	N
250	12	90	740	700	15	165	303	172	225	11.92	6.77	8.85	20.1	1	T1 post	N
404	6	77	360	340	TBA	90	218	170	190	8.58	6.69	7.48	14.1	0	T1 post	N
421	6	56	250	220	TBA	80	162	173	224	6.37	6.81	8.81	13.8	0	T1 post	N