

## DYNO Range 6v, 8v and 12v

PART No.	Voltage	Capacity @ 20 rate	CCA (SAE)	Plates per cell	Reserve capacity (minutes)	Weight (kg's)	Weight (lb's)	Dimensions (mm)			Dimensions (ins)			Engine start capability	
								L	W	H	L	W	H		
					75amp draw										
GC2C	6	225	NA	17	105	28	61	262	179	276	10.3	7.0	10.8	No	
GC2B	6	235	NA	19	125	30	67	262	179	276	10.3	7.0	10.8	No	
GC2H	6	245	NA	21	145	33	74	262	179	302	10.3	7.0	11.9	No	
3H	6	260	NA	21	135	33	74	295	179	302	11.6	7.0	11.9	No	
4H	6	315	NA	19	180	44	98	305	178	356	12.0	7.0	14.0	No	
L16	6	350	NA	19	210	54	118	314	181	425	12.3	7.1	16.7	No	
					25amp draw										
24M	12	85	570	13	190	19	42	260	171	225	10.2	6.7	8.8	Yes	
27M	12	100	640	15	190	22	50	327	168	227	12.9	6.6	8.9	Yes	
27MD	12	90	NA	11	200	23	52	327	168	227	12.9	6.6	8.9	No	
30HH	12	115	560	15	200	28	62	343	173	233	13.5	6.8	9.2	Yes	
30XHS	12	135	NA	13	220	32	70	343	173	233	13.5	6.8	9.2	NO	
31	12	115	700	17	190	26	58	330	173	238	13.0	6.8	9.4	Yes	
4D	12	193	950	19	395	45	100	518	221	249	20.4	8.7	9.8	Yes	
4DD	12	180	NA	19	385	52	114	518	221	249	20.4	8.7	9.8	No	
8DC	12	255	1250	31	495	64	141	527	279	248	20.7	11.0	9.7	Yes	
8DD	12	240	NA	27	485	66	146	527	279	248	20.7	11.0	9.7	No	
SSW	12	185	NA	11	90	53	116	394	178	362	15.5	7.0	14.2	No	
8VGC	8	167	NA	13	85	28	62	262	179	283	10.3	7.0	11.1	No	